



ColorBlend®

Euro-Coat

Polymer modified color topping

Description:

Polymer modified topping consisting of two components; powder and liquid admixture to make a spreadable mortar of sufficient thickness for stamping or profiling. There is usually not more than 1/2 inch thickness. This product comes in pastel colors, custom colors and standard gray for staining.

Uses:

Used with the aid of a liquid release agent for decorative stamped or textured finishes over existing flatwork such as driveways, patios, pool decks and many other uses.

Limitations:

This product is not designed to bridge cracks and it is recommended that all cracks and defects be repaired prior to installation. Not recommended for thicknesses over a 1/2 inch thick. Test a small area prior to application to determine proper bonding to substrate. Setting times on very hot days can be adjusted by cooling all components prior to mixing. A chemical retarder is also available. Avoid adding water as it will lighten the colors and produce color inconsistencies. This product must be sealed before placing into service, especially if used in wheel traffic areas or severe foot traffic.

Mixing:

For each 50 pounds of powder use 5 quarts of Acrylmax liquid polymer admix available in 5 gals. Pails.

Installation:

Start with a floor that is clean and free from grease, gum, contaminants. Sealers and coatings must all be removed. If surfaces are very smooth, mechanically profile the surfaces for better adhesion.

In a clean bucket, slowly add the bag of powder to a pre-measured amount of liquid polymer using a drill & paddle mixer until thoroughly mixed and free of lumps.

Mix a full unit at one time, partial mixed amounts will not provide consistent color results.

Spread the mixed product to the specified thickness and allow to become firm enough to support the imprint.

Apply the liquid release agent prior to placing stamp mat.

Work from the inside corners out; leaving room to apply the finish. Work in a continued process, mixing, pouring

and imprinting until all the work is completed.

Spike shoes may help when having to work in adjacent jointed areas.

Antiquing or other finishes can be applied as soon as it is safe to walk on the work without marring the work.

Wait 8 hours if sealing with water based sealers, 24 hours before sealing if using solvent based sealers, Always test an area first to determine if a sealer reaction can be seen, otherwise allow to fully set dry before sealing.

Packaging:

Supplied in 50 pound bags.

5 gallon pails of the wetting polymer.

Compliance:

4000 psi in 7 days. Meets ASTM C-979 for iron oxide colors

Clean-up:

Clean tools and equipment with soap and water.

Safety:

Clean all tools with soap and water. Avoid breathing dust while mixing. Contains Portland cement and silica sands Use a suitable respirator. Avoid prolonged skin contact. Use eye and skin protection especially when mixing product.

Liquid polymer does not contain hazardous ingredients but can cause skin, eye and mucous membrane irritation. Keep away from children and pets.

Contains Portland cement and silica that can cause burns and respiratory tract irritation. Constant cement and silica dust exposure should be avoided as it can cause a chronic respiratory condition.

T
O
P
I
C
S
I
D
E
S

Builders Construction Products
2761 NW 19th St, Pompano Beach, Fl. 33069
Tel: (954) 657-8812 Fax: (954) 657-8631
www.Builderscolor.com



We care about the environment



CONSTRUCTION PRODUCTS

Warranty:

When product is used according to directions; warranty is limited to the refund of the purchase price if deemed defective at manufacture. Products exceeding their shelf life are excluded from this warranty. Products are intended for industrial professional use by competent tradesmen with sufficient knowledge and experience on their use, installation and product suitability.

Builders Construction Products shall not be liable to the purchaser or any third party for labor costs, direct or indirect, any consequential damages related or due to the use, suitability or installation of this product.

No other warranties are implied. No one is authorized, employees of Builders Const. Prods. or otherwise to make modifications or misrepresentations of any warranties, other than what is expressed or covered in this published document. Purchaser and or the end user agrees to assume all responsibility for use, transport and proper disposal of un-used product and packaging. Keep from the reach of children and pets.

Do not dispose in drainage systems, lakes or bodies of water. Review MSDS for additional health information.